POLYMERIG

Technical Data: Issued: Sep.2006 Revision 2: Aug.2016, Page: 1	EP 1110DV Two-part Fast Cure Semi-fle	exible Epoxy Adhes	ive	
Product Description	EP 1110DV is a two component, fast curing, semi-flexible epoxy adhesive displaying excellent adhesion to metals and ceramics. EP 1110 DV has thermal shock resistance over a medium range of temperatures and its flexibility avoids any deformation between the adhesive articles.			
Features & Benefits	• Fast curing	• High adhesion to metals		
	• Semi-flexible	• Easy mix 1:1 ratio		
Applications	Fast curing epoxy adhesive for bonding and sealing.			
Typical Uncured Physical Properties	Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.			
	Base Resins	Base (A) Hardener (B)	Epoxy Resin Polyamide Resins	
	Appearance/Color	Base (A) Hardener (B)	translucent amber	
	Viscosity @ 25°C, mPa*s, ASTM-D-2393	Base (A) Hardener (B)	50000-70000 70000-95000	
	Density, g/cm ³ @ 25°C	Base (A) Hardener (B)	$\begin{array}{c} 1.16 \pm 0.05 \\ 1.05 \pm 0.03 \end{array}$	
	Mix Ratio (A:B), by vol.		1:1	
	Mix Viscosity, mPa*s	60	60000-80000	

http://www.polymer-g.com



Technical Data: Issued: Sep.2006 Revision 2: Aug.2016, Page: 2

EP 1110DV

Two-part Fast Cure Semi-flexible Epoxy Adhesive

Typical Cured Properties

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Color	amber	
Gel Time (2-3mm layer @ 25°C), min	10-15	
Curing (2-3mm layer @ 25°C), hr	3-4	
Final Curing @ 23°C, hr	24	
Hardness, Shore D	75-80	
Lap Shear Strength, etched Al, MPa	16-22	
Operating Temperature	-40°C to 110°C	

Storage	Store products at 18-30°C for maximum shelf life.
Packaging	1:1 50cc dual cartridges
Shelf Life	These products have a shelf life of 12 months in unopened dual cartridges
Limitation of Liability	Except where prohibited by law, Polymer-G and seller will not be liable for any loss or damage arising from the Polymer-G product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.